

## Příloha č.4 – Specifikace a technické parametry

### 4 x WASH LED pohyblivá hlava

Specifikace:

#### SOURCE:

120W RGBW (or more) COB LED LED WASH

#### PHOTOMETRIC DATA:

10 000 – 11 000 LUX 988 FC @9.8' (3m) (7° Full ON)

600 – 700 LUX 64 FC @9.8' (3m) (55° Full ON)

#### COLOR:

RGBW

Variable color temperature 2700-8000 K

#### EFFECTS:

RGBW Color Mixing

7° - 55° Beam Zoom Range

Electronic Strobe, Dimming and Variable Dimming Curves

64 Color Presets and 14 Unique Color Macros

motorized pan and tilt

#### CONTROL / CONNECTIONS:

4 DMX Channel Modes (19 Total Channels)

7 Button Control Panel and LCD Menu Display

RDM (Remote Device Management)

3pin/5pin DMX and powerCON In/Out

With Wired Digital Communication Network

#### ELECTRICAL / THERMAL:

AC 110-240V - 50/60Hz

140 W – 180 W Max Power Consumption

Multiple Unit Power Linking

-15°C to 45°C

**Tyto parametry splňuje např. Elation Fuze Wash Z120**

### 10 x LED PAR with motorized zoom

Specifikace:

#### SOURCE:

175W (or more) RGBW COB LED PAR

#### PHOTOMETRIC DATA:

15,000LUX 1396 FC @6.6 ft (2m) (Full ON 8°)

3,450 LUX 323 FC @6.6 ft (2m) (Full ON 35°)

**EFFECTS:**

8° - 35° Motorized Zoom

64 Color Presets and Color Macro Programs

Electronic Strobe

16-bit Variable Dimming Curve Modes

**COLOR:**

RGBW

Variable color temperature 2700-8000 K

**CONTROL / CONNECTIONS:**

12 DMX Channel Modes (14 Total Channels)

4 Button Control Panel and LCD Menu Display

RDM (Remote Device Management)

5pin DMX and powerCON TRUE1 In/Out

With Wired Digital Communication Network

**ELECTRICAL / THERMAL:**

AC 100-240V - 50/60Hz

200W Max Power Consumption

Multiple Unit Power Linking

5°F to 113°F (-15°C to 45°C)

**Tyto parametry splňuje např. Elation Fuze Par Z175**